



DIMENSIONS

	A	B	C	D	E	F	GMax	GMin	H	J	K	
<b>716 RJW</b>	79.25"	38.75"	9.63"	29.50"	17.25"	16.00"	22.75"	16.75"	70.25"	3.63"	15.75"	
<b>719 RJW</b>	98.50	44.00	11.00	32.00	22.00	22.00	29.00	17.00	98.50	11.00	15.25	
<b>722 RJW</b>	106.25	49.25	13.25	34.75	25.25	22.00	32.00	21.50	104.00	18.50	18.00	
<b>730 RJW</b>	134.25	60.00	18.00	50.00	30.00	28.00	40.00	24.00	134.00	10.00	23.50	
	L	M	N	O	P	R	SMax	SMin	TMax	TMin	U	V
<b>716 RJW</b>	18.50"	34.00"	22.00"	22.00"	14.00"	90°	12.75"	8.00"	18.50"	10.50"	19.00"	31.00"
<b>719 RJW</b>	20.75	38.00	30.00	23.00	13.50	90°	17.00	7.75	23.00	11.50	21.00	34.50
<b>722 RJW</b>	24.00	42.00	30.00	28.00	18.00	90°	18.25	10.00	24.50	13.25	24.50	38.00
<b>730 RJW</b>	29.25	50.00	42.00	37.00	20.00	90°	23.00	12.00	29.50	17.50	31.00	48.00

Dimensions are approximate and subject to change. Squeeze arm rotation standard as shown (right hand). Optional left hand to be specified at time of order.